

EON

NEW EXTENDED VERSION FOR LONG LEAFS

QK-E400 230Vac max 4m
QK-E400B 24Vdc max 4m

QK-E400FX 230Vac max 4m **HIGH SPEED**
QK-E400BFX 24Vdc max 4m **HIGH SPEED**

QK-E600 230Vac max 5m **NEW**



Key operated manual release
Sblocco manuale con chiave
Déblocage manuel avec la clé

THE DIFFERENCE IS IN THE DETAILS


EON IS THE STURDIEST GEARMOTOR OF ITS TYPE ON THE MARKET

Oversize deep-seated Seeger rings.


Union between the shaft and endless screw. Our system is one of the strongest on the market for gate motors.

Pressed fit sealed bearing.

Shaft and endless screw made of premium quality high tensile steel for strength and longevity and specially treated for external use and rust prevention.



Bearing housing fitted with hard metal crown to remove bearing and shaft stress and in turn, any wear on the aluminium tube.



Extremely sturdy tube support end ring, made of reinforced composite and giving the highest strength profile possible.



Installation limits per leaf <i>Limiti di impiego per anta</i> Contraintes d'utilisation				
	2 m	3 m	4 m	5 m
QK-E400 / FX	700kg	400kg	300kg	-
QK-E400B / FX	600kg	400kg	300kg	-
QK-E600	900kg	600kg	500kg	300kg

The values shown within the table above can be considerably reduced in windy areas.

I valori mostrati nella tabella sopra possono essere ridotti considerevolmente in zone ventose.

Les valeurs indiquées dans le tableau peuvent être considérablement réduites dans les zones venteuses.

TECHNICAL FEATURES	DATI TECNICI	DONNEES TECHNIQUES	QK-E400 QK-E400FX	QK-E400B QK-E400BFX	QK-E600
Power	<i>Alimentazione</i>	Alimentation	230Vac 50 / 60Hz	24Vdc	230Vac 50 / 60Hz
Current absorbed (motor) (A)	<i>Assorbimento motore (A)</i>	Intensité (A)	0,9 - 1,5	0,7 - 6,5	0,9 - 1,5
Power absorbed (W)	<i>Potenza assorbita (W)</i>	Puissance absorbée (W)	350	120	350
Capacitor (µF)	<i>Condensatore (µF)</i>	Condensateur (µF)	8	-	8
Protection level (IP)	<i>Grado di protezione (IP)</i>	Indice de protection (IP)	44	44	44
Opening time (sec)	<i>Tempo apertura (sec)</i>	Vitesse (sec)	20 10	20 10	20
Stroke (mm)	<i>Corsa (mm)</i>	Course (mm)	400	400	600
Max. thrust (N)	<i>Spinta max. (N)</i>	Couple max (N)	2200	2200	2200
Working temp. (°C Min/Max)	<i>Temp. di esercizio (°C Min/Max)</i>	Temp. de service (°C Min/Max)	-30/+70	-30/+70	-30/+70
Thermal cut-out (°C)	<i>Termoprotezione (°C)</i>	Protection thermique (°C)	150	-	150
Working cycle (%)	<i>Ciclo di lavoro (%)</i>	Cycle de travail (%)	40	100	40
Motor weight (kg)	<i>Peso motore (kg)</i>	Poids (kg)	6	6	6
Max. leaf length (m)	<i>Lunghezza max. anta (m)</i>	Longueur maxi vantail (m)	4	4	5

KIT

QK-E400KIT 230Vac max 4m (X2)
QK-E400BKIT 24Vdc max 4m (X2)
QK-E600KIT 230Vac max 5m (X2)

QK-E400KITFX 230Vac max 4m (X2) **HIGH SPEED**
QK-E400BKITFX 24Vdc max 4m (X2) **HIGH SPEED**

20 PCS PALLET



KIT LIGHT

KIT FULL

Pair of gearmotors with screw mount brackets + Control board with 433,92MHz receiver and Antenna + 4 channel transmitter + Pair of IR photocells + Flashing lamp + Key switch

Coppia di motoriduttori con staffe ad avvitare + Centrale con radiorecettore 433,92MHz e Antenna + Telecomando quadricanale + Coppia di fotocellule IR + Lampeggiante + Selettore a chiave

Deux motoréducteurs avec pattes de fixation à visser + Logique de commande avec récepteur radio 433,92MHz et Antenne + Émetteur 4 canaux + Jeu de photocellules IR + Feu clignotant + Sélecteur à clé

The content of the package may vary; consult the retailer
Il contenuto della confezione potrebbe variare; contattare il rivenditore
Le contenu du paquet peut varier; contactez revendeur

OPTIONALS



QK-CE220BATRL4

230V control board with 433,92MHz radioreceiver

Centrale 230V con radiorecettore 433,92MHz

Logique de commande 230V avec récepteur 433,92MHz

4,1(75)

24V control board with 433,92MHz radioreceiver

Centrale 24V con radiorecettore 433,92MHz

Logique de commande 24V avec récepteur 433,92MHz




QK-BPACK1

Backup battery

Batteria di backup

Batterie Backup



QK-ELS

12V vertical electrical lock

Elettroserratura 12V verticale

Serrure électrique 12V verticale




QK-BRAE400

Screw mount brackets (replacement)

Staffe ad avvitare (ricambio)

Pattes de fixation à visser (rechange)



For other optionals refer to the corresponding page of the catalogue

Per altri optionals andare alla relativa pagina del catalogo

Pour autres optionals se référer à la page correspondante du catalogue

